



Perfiles en aluminio



Diseño cuadrado del perfil frontal y las tapas



Iluminación LED integrada (opcional)

## CARACTERÍSTICAS

| MEDIDAS |                      |                    |                            |              |
|---------|----------------------|--------------------|----------------------------|--------------|
| SALIDA  | LÍNEA MÍNIMA MAQUINA | LÍNEA MÍNIMA MOTOR | LÍNEA MÍNIMA ENTRE PAREDES | LÍNEA MÁXIMA |
| 1500    | 1785                 | 1747               | 1842                       | 6000         |
| 1750    | 2036                 | 1999               | 2094                       | 6000         |
| 2000    | 2368                 | 2330               | 2425                       | 6000         |
| 2250    | 2619                 | 2581               | 2677                       | 6000         |
| 2500    | 2871                 | 2833               | 2928                       | 6000         |
| 3000    | 3454                 | 3416               | 3511                       | 6000         |
| 3500    | 3957                 | 3919               | 4015                       | 6000         |
| 4000    | 4460                 | 4422               | 4518                       | 6000         |




Clase II  
Según norma EN13561



| ABACO CLASIFICACION AL VIENTO |      |      |      |      |      |      |       |
|-------------------------------|------|------|------|------|------|------|-------|
| 3000                          | 3500 | 4000 | 4500 | 5000 | 5500 | 6000 | L / S |
|                               |      |      |      |      |      |      | 1500  |
|                               |      |      |      |      |      |      | 1750  |
|                               |      |      |      |      |      |      | 2000  |
|                               |      |      |      |      |      |      | 2250  |
|                               |      |      |      |      |      |      | 2500  |
|                               |      |      |      |      |      |      | 3000  |
|                               |      |      |      |      |      |      | 3500  |
|                               |      |      |      |      |      |      | 4000  |

49 km/h Clase III 38 km/h Clase II 29 km/h Clase I

## INSTALACIÓN



## ACCIONAMIENTO



MANUAL



MOTOR

OPCIONAL



MOTOR CSI  
( Solo inst. Frontal )

OPCIONAL



MOTOR  
(Solar-Brel)

OPCIONAL



MOTOR  
(Radio-SIMU)

OPCIONAL

## OPCIONES



LED  
( Brazos / Perfil Cofre )



TEJADILLO

## CERTIFICACIONES



MARCA CE



TORNILLERIA



LACADO


## COLORES BASE



## COLORES STANDARD



MÁS INFORMACIÓN  
APP



www.mecanotoldo.com

5076  32